

Technisches Datenblatt digitales

Funkkameraset DG60

www.securtech24.de

Specification:

	Item	Value
General	Frequency	ISM 2400~2483.5MHz
	Modulation	GFSK
	Antenna	Omni 3dBi
	Transmission distance	100m
	Operating temperature	-10°C – 60°C
	Operating humidity	20% - 80%
Receiver	Rx sensitivity	-81dBm (Typical)
	Video resolution	640 * 480 (VGA),320*240(QVGA),ZOOM
	Video signal output	NTSC/PAL Composite, 1V pk-pk, 75ohm (with audio)
	Image input channel	4 wireless channels
	Video mode	M-JPEG AVI
	Video frame rate	9~25fps
	Photo format	JPEG
	Storage media	SD
	Memory extension supported	16GB
	Power supply	AC 100 - 240V DC 12V 500mA
	Power consume	Max 160mA
	Dimensions	120 * 84 * 23MM
	Net Weight	190g (including adapter)
	Record overwrite	Optional
	Recording mode	Video recording and photo shooting
	Detection sensitivity	Max 5meters
	Record time display	Available
	Video system	NTSC\PAL adjustable

	Startup mode of recording video	Motion detection, scheduled and manual video recording
	Video file size	Approx. 10M/min
	Playback	Normal, fast forward, fast backward, pause
Camera	Sensor	CMOS 1/4"
	Resolution	640*480 pixels
	View angle	66°
	Water proof	IPX2
	Night vision Range	15meters
	Transmit output power	100mW
	Power supply	AC 100 - 240V DC 12V 500mA
	Power consume	Max 270mA
	Dimensions	110 * 75 * 82MM
	Net Weight	555g (including adapter)