

Technisches Datenblatt IP-Kamera KDM-6711BL

www.securtech24.de

Features:

- 1)Support full D1 resolution(PAL: 704*576, NTSC: 720*480) MPEG4 ip camera
- 2)Provide live video in D1 resolution, 25 Fps/PAL, 30Fps/NTSC
- 3)Support network real-time AVI dynamic video internet camera
- 4)Wireless transmission distance 300 feet
- 5)3 class sensitivity detection, transfer alarm and video via FTP or Email
- 6)GPIO outside equipment touch off alarm, video re-play, snapshot, DDNS
- 7)Compatible with microsoft windows media player network video
- 8)CPU:32Bit ARM9/ MPEG4 Encode Chip (D1)
- 9)One RS485 interface support remote PTZ function
- 10)Two groups digital signal input, one group control signal output, fit for IEEE 802.11g wireless network rule

Tech Parameter

Model	KDM-6711BL
Horizontal Resolution	420TVL
Image Sensor	1/3" SONY CCD
Lens	12MM fixed focus lens(default), 2.8-50mm fixed focus lens optional
S/N Ratio	>52dB
Network Connect	10/100MBase-T(RJ-45)
Video Compression	MPEG-4
Image	D1/2CIF/CIF/QCIF
Audio	One/Two-way audio optional
Wireless transmission	IEEE 802.11g wireless network
Communication Protocol	TCP/IP, ARP, ICMP, HTTP, SMTP, FTP, DHCP, DNS, DDNS, NTP, PPPoE
Transmission distance	100m
Operating System	Microsoft Windows 2000/XP
Clients Qty	Maximum 20 online visitors
Motion Detection	3 Level sensitivity (adjustable), auto send Email or FTP upload
Recording	Auto / Manual (send email or FTP upload when motion detected)
Camera Setting	Camera Name, Time, Date (auto time zone adjust, manual ajust) Frequency (60/50Hz)
PTZ Control	one RS485 interface (inside+ / outside-
Button Function	Built-in Restart / Default Setting
Operating Temperature	-5-50(working), -20-70(storing)
Power Supply	DC 12V 1A
Size	140(L) × 50(W) × 70(H)mm
Weight	Net 500g, Gross 700g
Packing List	Camera, Bracket, Lens, Power Supply, Manual, Carton Box