

Technisches Datenblatt IP-Kamera KDM-6742AL

www.securtech24.de

Model	KDM-6742AL
Horizontal Resolution	480TV Lines
Image Sensor	1/3" SONY Exview CCD
Effective Pixels	704*576, 650*480, 352*288, 320*240, 176*144, 160*120
Min. Illumination	0.001Lux/0Lux(IR ON)
Lens	6mm(default), 2.8-16mm lens optional
Lens mount	CS lens mount
Auto Iris Lens	Video/DC
Image Control	AEC, AGC, ABC, AWB
Electronic Shutter	Auto, 1/50(1/60)~1/100,000(sec)
S/N Ratio	>52dB
Waterproof	IP65
IR View Distance	20~100 meter optional
Network Connect	10/100MBase-T(RJ-45)
Transfer Speed	25Fps/PAL, 30Fps/NTSC
Video Compression	MPEG-4
Image	D1/2CIF/CIF/QCIF
Communication Protocol	TCP/IP, ARP, ICMP, HTTP, SMTP, FTP, DHCP, DNS, DDNS, NTP, PPPoE
DDNS	Built-in
PPPOE	Built-in ADSL auto-dial function
Wireless transmission	IEEE 802.11g wireless network
Transmission distance	300 feet without blocking
Operating System	Microsoft Windows 98/ME/2000/XP/2003
Audio	One/Two-way audio(optional)
User Manager	2 Level (Administrator / Client)
Clients Qty	Maximum 20 online visitors
Motion Detection	3 Level sensitivity (adjustable), auto send Email or FTP upload
Recording	Auto / Manual (send email or FTP upload when motion detected)
Camera Setting	Camera Name, Time, Date (auto time zone adjust, manual ajust) Frequency (60/50Hz)
Indication LED	Power Supply LED, Network LED, Wireless Network LED
PTZ Control	one RS485 interface (inside+ / outside-
Button Function	Built-in Restart / Default Setting
Operating Temperature	-5-50(working), -20-70(storing)
Humidity	0% ~ 80%
Power Supply	DC 12V 1.5A
Size	305(L) ×155(W) × 145(H)mm
Weight	Net 1400g, Gross 1610g
Packing List	Camera, Power Supply, Bracket, Manual, Carton Box