
Technisches Datenblatt IP-Kamera KDM-6781H

www.securtech24.de

Features:

- 1) Small size, hard to find, suitable to public place
- 2) Vandalproof shell use high rigidity PV alloy
- 3) Automatical IR LED start to suit low light environment
- 4) Support full D1 resolution (PAL: 704*576, NTSC: 720*480)
- 5) Provide live video in D1 resolution, 25Fps/PAL, 30Fps/NTSC
- 6) Support network real-time AVI dynamic video
- 7) 3 class sensitivity detection, transfer alarm and video via Email
- 8) Video re-play, snapshot, DDNS
- 9) Compatible with microsoft windows media player
- 10) CPU:32Bit ARM9/ MPEG4 Encode Chip (D1)

Tech Parameter:

Model	KDM-6781H	KDM-6781B
Horizontal Resolution	540TV Lines	420TV Lines
Image Sensor	1/3" SONY Exview CCD	
Effective Pixels	704*576,650*480,352*288, 320*240, 176*144, 160*120	
Min. Illumination	0.1 Lux	
Lens	Standard match 3.6mm/F1.2(6mm/12mm/16mm optional)	
Network Connect	10/100MBase-T(RJ-45)	
Transfer Speed	25Fps/PAL, 30Fps/NTSC	
Video Compression	MPEG-4	
Image	D1/2CIF/CIF/QCIF	
Audio	Single direction audio	
Communication Protocol	TCP/IP, ARP, ICMP, HTTP, SMTP, FTP, DHCP, DNS, DDNS, NTP, PPPoE	
PPPOE	Built-in ADSL auto-dial function	
Operating System	Microsoft Windows 98/ME/2000/XP/2003/Vista	
User Manager	2 Level (Administrator / Client)	
Clients Qty	Maximum 20 online visitors	
Motion Detection	3 Level sensitivity (adjustable), auto send Email or FTP upload	
Recording	Auto / Manual (send email or FTP upload when motion detected)	
Camera Setting	Camera Name, Time, Date (auto time zone adjust, manual adjust) Frequency (60/50Hz)	
Indication LED	Power Supply LED, Network LED, Wireless Network LED	
PTZ Control	one RS485 interface (inside+ / outside-)	
Button Function	Built-in Restart / Default Setting	
Operating Temperature	0°C-40°C(working), -20°C-60°C(storing)	
Power Supply	DC12V1A	
Packing List	Camera, Screw, CD, Color Box	