

LICE24N

- *Weatherproof IR camera with 3-Axis Bracket
- *IR LED: \varnothing 5X24PCS IR LED working distance:20M
- *Water resistance:IP66 Cable built-in bracket
- *Lens: Board Lens 3.6mm/F2.0
- *Dimension:86(W) x60(H) x55(D)mm Weight:400g



Model	LICE24NSHR	LICE24NSHD	LICE24NSHL	LICE24NSL
Image Sensor	1/3" SONY ICX639BK CCD	1/3" SONY ICX639BK CCD	1/3" SONY ICX839BK CCD	1/3" SONY ICX633BK CCD
Horizontal Resolution	650TVL Low Illumination, DWDR, OSD, 3D DNR, Sense-up	600TV Lines Low Illumination, DWDR, OSD, DNR	540TV Lines Low Illumination	420TV Lines Low Illumination
Pixels	PAL:795(H)x596(V), NTSC:811(H)x508(V)	PAL:795(H)x596(V), NTSC:811(H)x508(V)	PAL:752(H)x582(V), NTSC:768(H)x494(V)	PAL:500(H)x582(V), NTSC:510(H)x492(V)
TV System	PAL/NTSC			
IR LED	\varnothing 5X24PCS			
IR Series Distance	20M			
Lens	Board Lens 3.6mm/F2.0			
Sync System	Internal			
Usable Illumination	0.001Lux/F2.0			0.0005Lux/F2.0
S/N Ratio	\geq 54dB (AGC OFF)			\geq 48dB (AGC OFF)
Gamma Correction	0.45			
Video Out	Composite Signal (1.0Vp-p, 75 Ω)			
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec			
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec			
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max			
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max			
White Balance	Auto			
Power Source	DC12V 300mA			
Dimension	86(W) x60(H) x55(D)mm			
Weight	400g			