

LIED4

Features

Weatherproof IR camera

 IR LED: \varnothing 5X42PCS IR LED working distance: 40M

Water resistance: IP66 Cable built-in bracket

Lens: 4-9mm Manual Zoom Lens

Dimension: 295(W)x105(H)x95(D)mm


Specifications

Model	LIED40SHE	LIED40SHD	LIED40SHL	LIED40SL
Image Sensor	1/3" SONY ICX673AK CCD	1/3" SONY ICX639BK CCD	1/3" SONY ICX639BK CCD	1/3" SONY ICX633BK CCD
Horizontal Resolution	700TV Lines Low Illumination, Effio, ATR, OSD, NR	600TV Lines Low Illumination, WDR, OSD	540TV Lines Low Illumination	420TV Lines Low Illumination
Pixels	PAL:976 (H)× 494(V) NTSC :976 (H) × 582 (V)	PAL:795 (H)× 596(V) NTSC :811 (H) × 508 (V)	PAL:752(H)× 582(V), NTSC:768(H)× 494(V)	PAL:500(H)× 582(V) NTSC:510(H)× 492(V)
Usable Illumination	0.001 Lux/F2.0			0.0005 Lux/F2.0
TV System	PAL/NTSC			
IR LED	\varnothing 5X42PCS			
IR Series Distance	40 M			
Lens	4-9mm Manual Zoom Lens			
Sync System	Internal			
IR Status	Under 10 Lux By CDS			
IR Power On	CDS Auto Control			
S/N Ratio	\geq 65dB (AGC OFF)	\geq 54dB (AGC OFF)	\geq 48dB (AGC OFF)	
Gamma Correction	0.45			
Video Out	Composite Signal (1.0Vp-p, 75 Ω)			
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec			
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec			
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max			
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max			
White Balance	Auto			
Power Source	DC12V 300mA			
Dimension	295(W)x105(H)x95(D)mm			
Weight	1.3Kg			