

LIED50

Weatherproof IR camera with 3-Axis Bracket
 IR LED: \varnothing 5X65PCS IR LED working distance: 50M
 Water resistance: IP66 Cable built-in bracket
 OSD Menu controlled by cable button
 Lens: 2.8-12mm Manual Zoom Lens
 Dimension: 310(W)x200(H)x148(D)mm Weight: 1.4Kg



Model	LIED50SHR	LIED50SHD	LIED50SHL	LIED50SL
Image Sensor	1/3" SONY ICX839BK CCD	1/3" SONY ICX839BK CCD	1/3" SONY ICX839BK CCD	1/3" SONY ICX833BK CCD
Horizontal Resolution	650TVL Low Illumination, DWDR, OSD, 3D DNR, Sense-up	600TV Lines Low Illumination, DWDR, OSD, DNR	540TV Lines Low Illumination	420TV Lines Low Illumination
Pixels	PAL:795(H)x596(V), NTSC:811(H)x508(V)	PAL:795(H)x596(V), NTSC:811(H)x508(V)	PAL:752(H)x582(V), NTSC:768(H)x494(V)	PAL:500(H)x582(V), NTSC:510(H)x492(V)
TV System	PAL/NTSC			
IR LED	\varnothing 5X65PCS			
IR Series Distance	50M			
Lens	2.8-12mm Manual Zoom Lens			
Sync System	Internal			
Usable Illumination	0.001Lux/F2.0			0.0005Lux/F2.0
S/N Ratio	\geq 54dB (AGC OFF)			\geq 48dB (AGC OFF)
Gamma Correction	0.45			
Video Out	Composite Signal (1.0Vp-p, 75 Ω)			
Scanning System	PAL:625 Lines, 50 Field/Sec; NTSC:525 Lines, 60 Field/Sec			
Electronic Shutter Time	Auto: PAL 1/50-1/100,000Sec; NTSC 1/60-1/100,000Sec			
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max			
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max			
White Balance	Auto			
Power Source	DC12V 300mA			
Dimension	310(W)x200(H)x148(D)mm			
Weight	1.4Kg			