

## LIEDX50

Weatherproof IR camera with 3-Axis Bracket  
 IR LED:  $\varnothing$  5X65PCS, IR LED working distance: 50M  
 Water resistance: IP66 Cable built-in bracket  
 RS485/Video Line control Auto Focus Lens  
 4-9mm dynamic varifocal lens(standard)  
 5-15mm dynamic varifocal lens (Optional)  
 Dimension:310(W)x200(H)x148(D)mm,Weight:1.6Kg



Model	LIEDX50 SHD	LIEDX50 SL
Image Sensor	1/3" SONY ICX839BK CCD	1/3" SONY ICX633BK CCD
Horizontal Resolution	600TV Lines Low Illumination, DWDR, OSD,DNR	420TV Lines Low Illumination
Pixels	PAL:795 (H)x 596(V) NTSC :811 (H) x508 (V)	PAL:500(H)x582(V) NTSC:510(H)x492(V)
TV System	PAL/NTSC	
IR LED	$\varnothing$ 5X65PCS	
IR Series Distance	50 M	
Lens	4-9mm dynamic varifocal lens(standard) / 5-15mm dynamic varifocal lens (Optional)	
Sync System	Internal	
Iris Control	control:DC / VIDEO	
Usable Illumination	0.001Lux/F2.0	0.0005Lux/F2.0
S/N Ratio		
Gamma Correction	0.45	
Video Out	Composite Signal (1.0Vp-p, 75 $\Omega$ )	
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec	
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec	
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max	
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max	
White Balance	Auto	
Power Source	DC12V 300mA	
Dimension	310(W)x200(H)x148(D)mm	
Weight	1.6Kg	