

## LIK40

Weatherproof IR camera with 3-Axis Bracket  
 IR LED:  $\varnothing$  5X42PCS, IR LED working distance: 40M  
 Water resistance: IP66 Cable built-in bracket  
 OSD Menu controlled by cable button (standard)  
 OSD Menu controlled by RS485 (optional)  
 Lens: CS Lens 6mm/F2.0  
 Dimension: 228(W)x97(H)x82(D)mm , Weight: 1.4Kg



Model	LIK40SHE	LIK40SHR	LIK40SHD	LIK40SHL	LIK40SL
Image Sensor	1/3" SONY ICX673AK CCD	1/3" SONY ICX639BK CCD	1/3" SONY ICX639BK CCD	1/3" SONY ICX639BK CCD	1/3" SONY ICX633BK CCD
Horizontal Resolution	700TV Lines Low Illumination, Effio, ATR, OSD, DNR	650TVL Low Illumination, DWDR, OSD, 3D DNR, Sense-up	600TV Lines Low Illumination, DWDR, OSD, DNR	540TV Lines Low Illumination	420TV Lines Low Illumination
Pixels	PAL:1020(H)x596(V), NTSC:1020(H)x508(V)	PAL:795(H)x596(V), NTSC:811(H)x508(V)	PAL:795(H)x596(V), NTSC:811(H)x508(V)	PAL:752(H)x582(V), NTSC:768(H)x494(V)	PAL:500(H)x582(V), NTSC:510(H)x492(V)
TV System	PAL/NTSC				
Lens	CS Lens 6mm/F2.0				
Sync System	Internal				
Usable Illumination	0.001Lux/F2.0				0.0005Lux/F2.0
S/N Ratio	$\geq$ 65dB (AGC OFF)	$\geq$ 54dB (AGC OFF)			$\geq$ 48dB (AGC OFF)
Gamma Correction	0.45				
Video Out	Composite Signal (1.0Vp-p, 75 $\Omega$ )				
Scanning System	PAL:625 Lines, 50 Field/Sec; NTSC:525 Lines, 60 Field/Sec				
Electronic Shutter Time	Auto: PAL 1/50-1/100,000Sec; NTSC 1/60-1/100,000Sec				
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max				
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max				
White Balance	Auto				
Power Source	DC12V/500mA				
Dimension	228(W)x97(H)x82(D)mm				
Weight	1.4Kg				