

LIKT40

Weatherproof IR camera with 3-Axis Bracket
 IR LED: \varnothing 5X42PCS IR LED working distance: 40M
 Water resistance: IP66 Cable built-in bracket
 OSD Menu controlled by cable button (standard)
 OSD Menu controlled by RS485 (optional)
 4-9mm Manual Zoom Lens
 2.8-10mm Manual Zoom Lens optional
 Dimension: 228(W)x97(H)x82(D)mm ,Weight: 1.4Kg



Model	LIKT40SHE	LIKT40SHR	LIKT40SHD	LIKT40SHL	LIKT40SL
Image Sensor	1/3" SONY ICX873AK CCD	1/3" SONY ICX839BK CCD	1/3" SONY ICX839BK CCD	1/3" SONY ICX839BK CCD	1/3" SONY ICX833BK CCD
Horizontal Resolution	700TV Lines Low Illumination, Effio, ATR, OSD, DNR	650TVL Low Illumination, DWDR, OSD, 3D DNR, Sense-up	600TV Lines Low Illumination, DWDR, OSD, DNR	540TV Lines Low Illumination	420TV Lines Low Illumination
Pixels	PAL: 1020(H)x596(V), NTSC: 1020(H)x508(V)	PAL: 795(H)x596(V), NTSC: 811(H)x508(V)	PAL: 795(H)x596(V), NTSC: 811(H)x508(V)	PAL: 752(H)x582(V), NTSC: 768(H)x494(V)	PAL: 500(H)x582(V), NTSC: 510(H)x492(V)
TV System	PAL/NTSC				
Lens	4-9mm Manual Zoom Lens / 2.8-10mm Manual Zoom Lens optional				
Sync System	Internal				
Usable Illumination	0.001Lux/F2.0				0.0005Lux/F2.0
S/N Ratio	≥85dB (AGC OFF)	≥54dB (AGC OFF)			≥48dB (AGC OFF)
Gamma Correction	0.45				
Video Out	Composite Signal (1.0Vp-p, 75Ω)				
Scanning System	PAL: 625 Lines, 50 Field/Sec; NTSC: 525 Lines, 60 Field/Sec				
Electronic Shutter Time	Auto: PAL 1/60-1/100,000Sec; NTSC 1/60-1/100,000Sec				
Operation Temperature	-10°C ~ +50°C RH95% Max				
Storage Temperature	-20°C ~ +60°C RH95% Max				
White Balance	Auto				
Power Source	DC12V/500mA				
Dimension	228(W)x97(H)x82(D)mm				
Weight	1.4Kg				