

## LIKT90

Weatherproof IR camera with 3-Axis Bracket  
 IR LED:  $\varnothing$  5X72PCS, IR LED working distance: 60M  
 Water resistance: IP66 Cable built-in bracket  
 OSD Menu controlled by cable button (standard)  
 OSD Menu controlled by RS485 (optional)  
 4-9mm Manual Zoom Lens  
 2.8-10mm Manual Zoom Lens optional  
 Dimension:295(W)x120(H)x103(D)mm. Weight:1.7Kg



Model	LIKT90SHE	LIKT90SHR	LIKT90SHD	LIKT90SHL	LIKT90SL
Image Sensor	1/3" SONY ICX673AK CCD	1/3" SONY ICX639BK CCD	1/3" SONY ICX639BK CCD	1/3" SONY ICX639BK CCD	1/3" SONY ICX633BK CCD
Horizontal Resolution	700TV Lines Low Illumination, Effio, ATR, OSD, DNR	650TVL Low Illumination, DWDR, OSD, 3D DNR, Sense-up	600TV Lines Low Illumination, DWDR, OSD,DNR	540TV Lines Low Illumination	420TV Lines Low Illumination
Pixels	PAL:1020(H)x596(V), NTSC:1020(H)x508(V)	PAL:795(H)x596(V), NTSC:811(H)x508(V)	PAL:795(H)x596(V), NTSC:811(H)x508(V)	PAL:752(H)x582(V), NTSC:768(H)x494(V)	PAL:500(H)x582(V) NTSC:510(H)x492(V)
TV System	PAL/NTSC				
Lens	4-9mm Manual Zoom Lens / 2.8-10mm Manual Zoom Lens optional				
Sync System	Internal				
Usable Illumination	0.001Lux/F2.0				0.0005Lux/F2.0
S/N Ratio	≥85dB (AGC OFF)	≥54dB (AGC OFF)			≥48dB (AGC OFF)
Gamma Correction	0.45				
Video Out	Composite Signal (1.0Vp-p, 75Ω)				
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec				
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec				
Operation Temperature	-10°C ~ +50°C RH95% Max				
Storage Temperature	-20°C ~ +60°C RH95% Max				
White Balance	Auto				
Power Source	DC12V500mA				
Dimension	295(W)x120(H)x103(D)mm				
Weight	1.7Kg				