

LPTM10X

- ★Vandalproof Mini PTZ Speed Dome camera
- ★Pan range: 0°~360° Continue (Not 355°)
- ★Tilt range: 0°~90° Flip
- ★Pan Speed: Max 50°/sec Preset: 16
- ★Weatherproof Outdoor IP66
- ★RS485, Pelco D/P supported
- ★10X(f=3.8~38mm)
- ★Size: 121x177mm Weight: 2.8Kg



Model	LPTM10XCG	LPTM10XSG
Image Sensor	10X, 1/4" Super HAD Color Sony CCD, 10X(f=3.8~38mm)	SAMSUNG 10X SDM-100, 1/4" Super HAD Color CCD, ICR, 10X(f=3.8~38mm)
Horizontal Resolution	Color 480TVL	Color 500TVL,Black 570TVL
Pixels	PAL:976 (H)× 494(V) NTSC :976 (H) ×582 (V)	PAL:795 (H)× 596(V) NTSC :811 (H) ×508 (V)
TV System	PAL/NTSC	
Lens	10X optical zoom lens(f=3.8~38mm)	
Sync System	Internal	
Usable Illumination	0.001Lux/F2.0	
S/N Ratio	≥65dB (AGC OFF)	≥54dB (AGC OFF)
Gamma Correction	0.45	
Video Out	Composite Signal (1.0Vp-p, 75Ω)	
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec	
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec	
Operation Temperature	-10℃ ~ +50℃ RH95% Max	
Storage Temperature	-20℃ ~ +60℃ RH95% Max	
White Balance	Auto	
Power Source	DC12V 700mA	
Dimension	121x177mm	
Weight	2800g	