

LVDP

Vandalproof Dome Camera
 SONY/SHARP Color CCD
 3-Axis bracket built-in
 OSD Menu controlled by cable button (standard)
 OSD Menu controlled by RS485 (optional)
 With bracket add
 Lens:4-9mm Manual Zoom Lens
 Dimension : \varnothing 118x 98(H) mm Weight:600g



Model	LVDP SHE	LVDP SHR	LIRDBSHD	LIRDBSHL	LVDP SL
Image Sensor	1/3" SONY ICX673AK CCD	1/3" SONY ICX639BK CCD	1/3" SONY ICX639BK CCD	1/3" SONY ICX639BK CCD	1/3" SONY ICX633BK CCD
Horizontal Resolution	700TV Lines Low Illumination, Effio, ATR, OSD, DNR	650TVL Low Illumination, DWDR, OSD, 3D DNR, Sense-up	600TV Lines Low Illumination, DWDR, OSD, DNR	540TV Lines Low Illumination	420TV Lines Low Illumination
Pixels	PAL:1020(H) \times 596(V), NTSC:1020(H) \times 508(V)	PAL:795(H) \times 596(V), NTSC:811(H) \times 508(V)	PAL:795(H) \times 596(V), NTSC:811(H) \times 508(V)	PAL:752(H) \times 582(V), NTSC:768(H) \times 494(V)	PAL:500(H) \times 582(V), NTSC:510(H) \times 492(V)
TV System	PAL/NTSC				
Lens	4-9mm Manual Zoom Lens				
Sync System	Internal				
Usable Illumination	0.001Lux/F2.0			0.0005Lux/F2.0	
S/N Ratio	\geq 85dB (AGC OFF)	\geq 54dB (AGC OFF)			\geq 48dB (AGC OFF)
Gamma Correction	0.45				
Video Out	Composite Signal (1.0Vp-p, 75 Ω)				
Scanning System	PAL:625 Lines, 50 Field/Sec; NTSC:525 Lines, 60 Field/Sec				
Electronic Shutter Time	Auto: PAL 1/50-1/100,000Sec; NTSC 1/60-1/100,000Sec				
Operation Temperature	-10 $^{\circ}$ C ~ +50 $^{\circ}$ C RH95% Max				
Storage Temperature	-20 $^{\circ}$ C ~ +60 $^{\circ}$ C RH95% Max				
White Balance	Auto				
Power Source	DC12V 450mA				
Dimension	\varnothing 118x 98(H) mm				
Weight	600g				