

LPTM



Features

- ★Vandalproof Mini PT Speed Dome camera
- ★Pan range: 0° ~360° Continue (Not 355°)
- ★Tilt range: 0° ~90° Flip
- ★Pan Speed: Max 50° /sec Preset: 16
- ★Weatherproof Outdoor IP66
- ★RS485, Pelco D/P supported
- ★Lens: 4-9mm Manual Zoom Lens



Specifications

Model	LPTMSHE	LPTMSHD	LPTMSHL	LPTMSL
Image Sensor	1/3"SONY			
Horizontal Resolution	ICX673AK CCD,700TV Lines Low Illumination, Effio, WDR, OSD, NR	ICX639BK CCD, 600TV Lines Low Illumination, WDR, OSD	ICX639BK CCD, 540TV Lines Low Illumination	ICX633BK CCD, 420TV Lines Low Illumination
Pixels	PAL:795 (H)× 596(V) NTSC :811 (H) × 508 (V)			PAL:500(H)× 582(V) NTSC:510(H)× 492(V)
TV System	PAL/NTSC			
Lens	4-9mm Manual Zoom Lens			
Sync System	Internal			
Usable Illumination	0.001Lux/F2.0			0.01Lux/F2.0
S/N Ratio	≥ 48dB (AGC OFF)			
Gamma Correction	0.45			
Video Out	Composite Signal (1.0Vp-p, 75Ω)			
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec			
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec			
Operation Temperature	-10°C ~ +50°C RH95% Max			
Storage Temperature	-20°C ~ +60°C RH95% Max			
White Balance	Auto			
Power Source	DC12V 700mA			
Dimension	121x177mm			
Weight	2500g			